


Uticor Lite Marquee Selection and Specifications



UTLMR-1L20C UTLMRH-1L20C



UTLMT-1L20C



UTLMR-1L40C UTLMRH-1L40C



UTLMT-1L40C

Uticor Lite Marquee Model Specifications				
Part Number	UTLMR-1L20C UTLMR-1L20C-E UTLMR-1L20C-D UTLMR-1L20C-P UTLMRH-1L20C UTLMRH-1L20C-E UTLMRH-1L20C-D UTLMRH-1L20C-P	UTLMT-1L20C UTLMT-1L20C-E UTLMT-1L20C-D UTLMT-1L20C-P	UTLMR-1L40C UTLMR-1L40C-E UTLMR-1L40C-D UTLMR-1L40C-P UTLMRH-1L40C UTLMRH-1L40C-E UTLMRH-1L40C-D UTLMRH-1L40C-P	UTLMT-1L40C UTLMT-1L40C-E UTLMT-1L40C-D UTLMT-1L40C-P
Display Type for Indoor	RED LED	TRI-Color LED	RED LED	TRI-Color LED
Display Type for "H"	RED Sunlight Readable		RED Sunlight Readable	
Specification	1 Line of 20 Char (2")		1 Lines of 40 Char (2")	
Max. Viewable Distance	100 Feet with 2" Characters		200 Feet with 4" Characters	
Power Consumption	15 watts	28 watts	30 watts	60 watts
Agency Approvals	UL, CUL, CE, pending			
Enclosure	NEMA12			
Operating Temperature	0° to 60° C Ambient			
Storage Temperature	-40° to 95° C Ambient			
Humidity	10% to 95% RH, Non-Condensing			
Input Power	110/220 VAC, 47-63Hz			
Electrical Interference	NEMA ICS 2-230 Showering Arc Test			
Electrical Tolerance	ANSI C37.90a-1974 (SWC) Surge With-Stand Capability Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Communications	Port 1 RS232; Port 2 RS422/485			
External Dimensions	36.9" x 4.8" x 2.8" (936.44 x 121.43 x 69.85mm)		72.1" x 5.4" x 2.8" (1831.31 x 106.35 x 69.85mm)	
Weight	4.5 lbs	4.8 lbs	8 lbs	8.5 lbs